

# Rions Type III- RO Basic



## Features

- Produces the ASTM water grade III, IV
- Wide graphic LCD display
- Easy to use and convenient maintenance
- Compact design
- Printer for data output
- ISO9001 and certified CE

## Specification

Model	RO Basic 10	RO Basic 20
<b>Product Rate (up to)</b>	10L/Hr	20L/Hr
<b>Product Quality</b>	1-25us/cm	
<b>Display</b>	Wide graphic LCD (128X64 digits)	
<b>System Functions &amp; Monitoring</b>	<ul style="list-style-type: none"> <li>● Inlet conductivity (at 25°C)</li> <li>● Product conductivity (at 25°C)</li> <li>● Rejection ratio(%)</li> <li>● Filter Pack exchange message</li> <li>● RO Membrane cleaning timer</li> <li>● Automatic drain for low quality</li> </ul>	
<b>Utilities</b>	120/240V, 50/60Hz, 1.6A	
Electrical Power	W330 x D455 x H510 (mm)	
Dimension	18kg	18.5kg
Operating Weight		
<b>Standard Accessories</b>	<ul style="list-style-type: none"> <li>· 1 Pre- Pack</li> <li>· 1 RO Membrane(RO Basic 10 Model)</li> <li>· 2 RO Membrane(RO Basic 20 Model)</li> <li>· 1 Operation manual</li> <li>· 1 Power cable &amp; tubing kit</li> </ul>	
<b>Optional Accessories</b>	<ul style="list-style-type: none"> <li>● 35L Reservoir tank with level sensor</li> <li>● Printer with interface for data output</li> </ul>	

## Flow Diagram

